

Type 1 Passiv Plus

gültig ab / valid from
10.02.2025

0,33 W/m²K

U-Wert
U-value

0,19 W/m²K

U-Wert mit ISO-Oberdeckel
U-value with ISO upper lid



	A	A	B	C	D	E
	Lukenkasten frame size	Rohbaumaß ceiling opening size	lichte Raumhöhe floor to ceiling height	Ausklappraum fold-out space	Grundmaß basic size	Schwenkraum Oberdeckel nach hinten swivel range top cover to the rear
Version	L x B x H in mm	L x B in mm	in mm	in mm	in mm	in mm
110 / 70	1090 x 690 x 455	1100 x 700	max. 2650	600	1200	1490
120 / 70	1190 x 690 x 455	1200 x 700	max. 2700	500	1200	1590
130 / 70	1290 x 690 x 455	1300 x 700	max. 2700	400	1200	1690
140 / 70	1390 x 690 x 455	1400 x 700	max. 2700	300	1200	1790
140 / 70	1390 x 690 x 455	1400 x 700	max. 3000*	400	1250	1790

*bei Raumhöhe 3000 mm ist keine Treppenverlängerung möglich / no staircase extension possible for room heights of 3000 mm

EI₂60

Brandhemmende Wirkung
fire-retardant effect

